

# VIDEO WALL LCD NARROW BEZEL

US-PJ4602



**USER**<sup>®</sup>

**SPECIAL DISPLAY**

Creating Better Visions  
[Http://en.usersdt.com](http://en.usersdt.com)

Excellent HD image.

Ultra narrow bezel design.

Intelligent error correction & compensation.

Easy 178 degrees viewing angles.

# FUNCTIONS & PARAMETERS

<b>Specifications</b>	
Model No.	US-PJ4602
Panel Size	46" LCD Screen(with narrow bezel 5.3mm,with 500 nits LED Backlight)
Aspect Ratio	16:09
Max Resolution Support	1920x1080
Pixel Pitch	0.63(H)×0.63 (V)
Color	8Bit, 16.7M
Brightness (nits)	500cd/m2
Contrast	4000:1
Visual Angle (H/V)	178°(H) / 178°(V)
Response Time	<=8ms
Life(hrs)	>60,000(hrs)
<b>Image</b>	
Aspect ratio	16:09
Quality compensation technology	LTI, CTI
Motion compensation technology	AUTO MOVE
Filter	3D comb filtering, digital noise reduction
Video standard	PAL, NTSC
<b>Video Wall Controller(Built-in each Screen)</b>	
Digital signal input	HDMI×1; 1920x1080@60Hz backward compatible
Computer signal input	VGA(DB-15) ×1; 1920x1080@60Hz backward compatible
Digital signal input	DVI(DVI-I)×1; 1080P(1920×1080) backward compatible
RJ45	2
Computer centralized control interface	RS232
<b>Power</b>	
Power Supply	AC100V ~240V
Maximum Power Consumption	280W
Standby Power Consumption	<=3W
<b>Structure</b>	
Border dimension	Top: 3.6mm; bottom 1.7mm; Left: 3.6mm; Right: 1.7mm
External dimension	1024mm × 578mm × 141mm
Net weight	22kg
Shell material	Metal shell, anti-static,anti-magnetic,anti-strong electric field interference
Installation way	Wall mount, floor standing mount,hanging mount
<b>Temperature</b>	
Working temperature	0℃ ~50℃
Storage temperature	-20℃ ~65℃
Working Humidity	20%-80%
<b>Package weight and dimension</b>	
Gross weight(2 sets in one honeycomb carton)	61kg
honeycomb carton(2 in 1)	1400x470x890mm

# DIMENSIONS

